




MODEL: ANG/D3502-SGL-XX-TOP-10
 WHERE "XX" DESIGNATES THE NUMBER OF VALVE STATIONS

REV		CN #		REVISION CHANGE	DATE
X1		N/A		DRAWN	02 JAN 01



MODEL FEATURES:

- ACCOMMODATES ANGAR D350 TYPE LIQUID VALVES USED IN A 2 PORT CONFIGURATION.
- SPECIFY FROM 2 TO 12 VALVES. ADD OR SUBTRACT .73" (18.54 MM) OF MANIFOLD LENGTH PER VALVE.
- TOP PORTED FOR EASY ACCESS AND MINIMUM REQUIRED SPACE.
- VALVES ARE MOUNTED VIA EXCLUSIVE 'NO-STRESS' BONDED-IN BRASS INSERTS.
- MULTIPLE INLET PORTS PROVIDE FOR DAISY CHAINING OR SUPPLY PRESSURE DISTRIBUTION.
- INTERNAL CHANNELS ARE .063" WIDE x .063" DEEP, BRILLIANTLY POLISHED AND WITHSTAND PRESSURE OVER 125 P.S.I.



NOTES:

1. MANIFOLDS ARE SUPPLIED WITHOUT ANY HARDWARE OR VALVES. THE COMPONENTS SHOWN ARE FOR ILLUSTRATION PURPOSES ONLY.
2. ALL PORTS ARE THREADED #10-32 UNF - 2B. M5.0 THREADS ARE AVAILABLE ON SPECIAL REQUEST.
3. MOUNTING HOLES ARE .156 DIAMETER FOR #6 SCREWS. USE OF .375 DIAMETER X .040 THICK (MIN) NYLON WASHERS UNDER THE MOUNTING SCREW HEADS ARE HIGHLY RECOMMENDED.
4. MANIFOLD MATERIAL IS POLISHED ACRYLIC. CLEAR (BLuish TINT) P.V.C. IS ALSO AVAILABLE ON SPECIAL ORDER AT INCREASED PRICE.
5. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

MicroAdvances

6073 N.W. 167th STREET, BLDG. C-21
 MIAMI, FL. USA 33015 • (305) 556-4801

NAME: ANG/D3502-SGL-04-TOP-10
PART/DWG NO: 600299 **REV:** A
ASSEMBLY: N/A
DWN BY: J.W. **DATE:** 02 JAN 01
DESIGNED BY: XX
REF: **ANG/D3502 (2 PORT)**

ASCO/ANGAR, Cedar Knolls, NJ 07927-2098

SCALE: 1 : 1 @ 7.9 X 10.4 **SHEET:** 1 OF 1